# Toward Accelerated Unstructured Mesh Particle-in-Cell

Gerrett Diamond<sup>1</sup>, Cameron W. Smith<sup>1</sup>, Chonglin Zhang<sup>1</sup>, Eisung S. Yoon<sup>2</sup>, Gopan Gopakumar<sup>1</sup>, Onkar Sahni<sup>1</sup>, Mark S. Shephard<sup>1</sup>

<sup>1</sup>Scientific Computation Research Center Rensselaer Polytechnic Institute

<sup>2</sup>Ulsan National Institute

November 18, 2019

#### Outline


Mesh-Based PIC

2 PUMIPic

3 PUMIPic Tests

# Unstructured Mesh Particle-In-Cell (PIC) Simulation

- PIC simulations iterate over four main operations per time step:
  - Particle Push particle positions are updated based on mesh fields.
  - Particle-to-Mesh based on the new particle positions, mesh fields are updated.
  - Field Solve domain level PDEs to update global mesh fields.
  - Mesh-to-Particle particle information is updated for the next push operation.
- Two simulations of interest:
  - XGC 3D PIC simulation using a 2D mesh representing polodial planes.
  - GITR 3D mesh PIC monte-carlo simulation.



XGC tokamak simulation, 2 polodial planes

#### Mesh-based PIC

- Traditional approach to PIC is to primarily store particles
  - ▶ Each particle knows the mesh element it is within.
  - A copy of the mesh is maintained on all processes.
- Mesh-based PIC is when the primary storage is the mesh.
  - ▶ Each element maintains a list of the particles inside the element.
  - Easier to maintain a distributed mesh.
- Goal is to develop mesh-based PIC framework that operates efficiently on GPUs.

#### Outline

Mesh-Based PIC

2 PUMIPic

PUMIPic Tests

# PUMIPic - Parallel Unstructured Mesh Infrastructure for Particle-in-cell


- Provides a set of data structures and algorithms for unstructured mesh-based PIC.
- Uses Kokkos for GPU support
- Includes:
  - GPU-based Particle Structure
  - GPU-based PIC Mesh Structure
  - Adjacency Search
  - Mesh Field Synchronization
  - Gyro-Average Scatter

#### Particle Data Structure

- Particles dominate computation and memory usage.
- Particle data structures need to account for:
  - grouping particles by element for efficient mesh-particle interactions.
  - **②** different simulations requiring different information per particle.
- For performance on GPUs the particle structure must be:
  - distributable to threads evenly.
  - 2 mapped to the hardware memory layout and access pattern.

# Particle Data Structure - Sell-C-Sigma (SCS)

- Rotated CSR structure
- Groups rows into chunks mapped to the hardware of GPU
- Padding improves access pattern at the cost of memory
- Performs sorting of rows to reduce padding
- Vertical slicing improves distribution of work



From left to right:

Adjacency Matrix, CSR, SCS with no sorting, full sorting, vertical slicing "SlimSell: A Vectorized Graph Representation for Breadth-First Search", M. Besta et al.

## Particle Data Structure - Sell-C-Sigma

- For PIC, the SCS is used with
  - A row per mesh element.
  - ▶ Each entry in the row represents a particle within the element.
- Application defined particle data is stored in identical SCS structures.
- Custom parallel\_for hides indexing complexity for GPU execution.

#### **Algorithm** GPU kernel launch to operate on each particle

```
lambda = LAMBDA(element_id, particle_id, mask) {
if mask is true then
Perform per particle operation
}
scs.parallel_for(lambda);
```

• Structure must be rebuilt whenever particles move to new elements.

## Particle Data Structure - Rebuild/Migration

- Regroups particles by element based on updated particle positions after push.
- Creates new SCS by copying particle data from old SCS.
  - ▶ Additionally supports adding and removing particles from the structure.
- Each process in a multi-process simulation has its own SCS instance.
- Particles can be migrated between processes prior to rebuild.
  - Migrations are treated as particles leaving and joining the structures.

#### PIC Mesh Structure

- PUMIPic uses Omega\_h for multiprocess unstructured mesh representation on GPUs.
  - https://github.com/SNLComputation/omega\_h
- Ensure particles are not pushed off process by duplicating mesh elements.
- Mesh partition is used to setup core regions of each part.
- The core plus buffered mesh entities is called a PICpart.



Core region



Buffer around core

## PIC Mesh Structure - PICparts


- First approach to PICparts was to keep *n* layers of buffer elements off the core.
- This had memory problems when scaling due to maintaining remote information.
- New approach is to buffer entire parts around core region.
- May buffer parts not directly adjacent if too close to the boundary.
  - Picpart for core A will buffer C.
- Uses a global numbering scheme to avoid keeping remote information.



PICpart for core region A

## PIC Mesh Structure - Adjacency Search

- After particles are pushed, some particles' new position will be in a new element.
- In order to locate the new parent element an adjacency walk is performed.
- Adjacency search is performed by a combination of barycentric coordinates and ray tracing.
- Adjacency search is fast since particles only move a small number of elements per push.
- If a particle's path crosses a geometric model face, the collision is captured for application specific wall interactions.




Adjacency search for a particle in a 2D triangular mesh

## PIC Mesh Structure - Field Synchronization

- Mesh field synchronization is required to update information on buffered regions of the mesh.
- Take advantage of full part buffering by using arrays ordered consistently across parts.
- Uses fan-in fan-out approach for each core region.
- Lower dimension entities on PICpart boundaries may not be part of a fully buffered core.
  - Halo exchanges are used for these entities.
- When the full mesh is buffered on every process a reduction across all ranks is used.

# PIC Mesh Structure - Gyro Averaging

- Essential for particle-to-mesh and mesh-to-particle operations for some PIC codes.
  - Particles on V scatter contributions to gyro rings (g<sub>0</sub>, g<sub>1</sub> on R) around each vertex of the parent element
  - Points along the gyro rings are projected along field lines to forward (P1) and backward (P0) planes.
  - Contributions of each gyro ring point are divided to the vertices of the element projected to.
- Build a mapping during initialization from each gyro ring point to projected mesh vertices.



#### Outline


Mesh-Based PIC

PUMIPic

3 PUMIPic Tests

## Pseudo-XGC Experiments


- Initial testing performed on ORNL Summit system.
  - ▶ One MPI process per GPU.
  - All six GPUs used per node.
- Performance studies performed on a pseudo-XGC simulation.
  - Particles move in a regular elliptical motion.
  - Gyro averaging does not project along field lines.
- 120 thousand element mesh run on up to 108 GPUs.
- Weak-scaling study up to 48 million particles per GPU (PPG).
- Partitioned based on flux face classification.
- PICparts consist of full mesh copies.



XGC mesh with 24 thousand triangles and 58 geometric model faces defined by magnetic field flux curves.

#### Pseudo-XGC Results


- From 6 GPUs to 108 GPUs, push rate increases by a factor of 18 for 48 million PPG.
- 100% weak-scaling efficiency for 16-48 million PPG on 108 GPUs.
- Weak-scaling over 100% is attributed to strong scaling of elements.



Push rate (left) and weak scaling (right) for 2 million to 48 million particles per GPU on up to 108 GPUs. Higher is better.

### **Operation Timing**

- SCS rebuild is the most expensive operation.
- Particle migration is the biggest loss in scaling.



Time spent in each operation with MPI barriers to isolate operations. Lower is better.

## Summary

- PUMIPic library supports mesh-based PIC running on GPUs.
- Particle weak scaling showed 100% efficiency on up to 108 GPUs.
- Performance is restrained by rebuild operation.
  - Optimization possible by shuffling data when possible to avoid a full rebuild.
- Load balancing will be needed for further scaling.





Questions?



Part of the SciDAC supported project, "Unstructured Mesh Technologies for Fusion Simulation Codes"

In collaboration with:

- FASTMath SciDAC Institute
- High-Fidelity Boundary Plasma Simulation SciDAC Partnership
- Plasma Surface Interactions SciDAC Partnership
- COPA: ECP Co-Design Center for Particle Applications